

1	2	3	4	5
CORRUGATED PAPER BOARD REEL LABEL		PACKING DIRECTION E CARRIER TAPE IS EMPTY THE CARRIER TAPE WITH 300PCS I 192mm 7200mm 2.00±0.10 24.00±0.10 192mm 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	144mm 336mm Round Sprocket Hold	A 32mm 32mm
DRYING AGENT WATER PROOF BAG	FITTING TAPE	PACKING DIRECTION DIRECTION OF UNREELING REEL LABEL REEL	REEL LABEL COVER TAPE	E
TRIANCLE CARDBOARD	CARTON CARTON 340 x 340 x H 290mm		OTES . MATERIALS: PS ANTI STATIC . PACKING:TAPE REEL(400PCS/REEL,2100PCS/CAR All Material in According With The RoHS Environ Related Substances List Controlled.	 C
RoHS Compliant G F E D C B A	APPROVAL: NPr	.XX = 1/_ 0.15	WÜRTH ELEKTRONIK DESCRIPTION: WR-COM - USB 3.0 REVERS HORIZONTAL TYPE A WITH OFFSET 0.14 M	
REV DATE FILE	BY	DRAW: AS	WERI PART NO: 692 121 130 100	

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Р
A	10-SEP-14	PDF	QL		SHEET: 3/3	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			