


STRADA-2X2CSP-VSM

IESNA Type V (square) for wide area lighting such as car parks.


TECHNICAL SPECIFICATIONS:

Dimensions	50.0 mm
Height	5.8 mm
Fastening	pin, screw
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	5.6 kg
Quantity in Box	800 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
STRADA-2X2CSP-VSM	Lens	PMMA	clear




PHOTOMETRIC DATA (MEASURED):





LED NVSxE21A
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.510 cd/lm
 Required components:





LED SMJQ-D36W12Mx
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.430 cd/lm
 Required components:




LED SMJQ-D48W16AA-XX
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.340 cd/lm
 Required components:



LED Z8Y19 2x2 cluster
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.340 cd/lm
 Required components:




PHOTOMETRIC DATA (MEASURED):



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LH181A
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.470 cd/lm
Required components:




SAMSUNG

LED LH181B
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.480 cd/lm
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y19
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.500 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)