


NOTES: UNLESS OTHERWISE SPECIFIED

- P/N: XRCOLOR  
HOUSING & PLUNGER: MOLDED NYLON TYPE 6,6.  
AVAILABLE IN TEN COLORS.  
CONTACT BLADE: BERYLLIUM COPPER PER QQ-C-533. GOLD PLATED PER MIL-G-45204 B TYPE 1 0.00001 [0.000254] THICK MINIMUM.  
SPRING: STAINLESS STEEL TYPE 302.

- P/N: W-600/COLOR  
18AWG 65X36 TINNED COPPER  
0.144 [3.66] O.D. PVC INSULATION  
AVAILABLE IN TEN COLORS.

- PERFORMANCE  
MAXIMUM CURRENT: 4.0 AMPS  
MAXIMUM VOLTAGE: 5000 W.V.D.C.  
MAXIMUM TEMPERATURE: 221°F (105°C)



LTR	DESCRIPTION	REVISIONS	DATE	APPROVED

		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES		CONTRACT NO.		DESCRIPTION	
		.XX ± .XXX ±		APPROVALS		MINI-HOOK (XR) TO LEAD ONLY	
		MATERIAL SEE NOTE.		DRAWN R.L.		CODE IDENT NO. 08505	
		FINISH SEE NOTE.		APPROVED BY		DRAWING NO. 613XR	
		APPLICATION USED ON		DATE 10/10		SCALE 1:1	
		DO NOT SCALE DRAWING				SHEET 1 OF 1	

**E-Z-HOOK** DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK. DIV. OF TEKTEST INC. MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.