

## Panel feed-through terminal block - PWO 16-POT - 1705653


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel feed-through terminal block, Connection method: Push-in spring connection, Cable lug connection, Number of positions: 1, Load current : 76 A, Cross section: 1.5 mm<sup>2</sup> - 16 mm<sup>2</sup>, AWG 14 - 4, Width: 12 mm, Color: gray



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 790840
GTIN	4046356790840
Weight per Piece (excluding packing)	29.200 g
Custom tariff number	85369010
Country of origin	China

### Technical data

#### General

Number of levels	1
Number of connections	2
Nominal cross section	16 mm <sup>2</sup>
Color	gray
Insulating material	PA
Flammability rating according to UL 94	V0
Maximum load current	76 A
Rated surge voltage	8 kV
Degree of pollution	3
Overvoltage category	III
Insulating material group	I

# Panel feed-through terminal block - PWO 16-POT - 1705653

## Technical data

### General

Connection in acc. with standard	IEC 60947-7-1
Nominal current $I_N$	76 A
Maximum load current	76 A
Nominal voltage $U_N$	1000 V
Open side panel	No
Number of positions	1

### Dimensions

Width	12 mm
Plate thickness	1 mm ... 6 mm

### Connection data

Connection side	Outside
Connection method	Push-in spring connection
Conductor cross section solid min.	1.5 mm <sup>2</sup>
Conductor cross section solid max.	16 mm <sup>2</sup>
Conductor cross section flexible min.	1.5 mm <sup>2</sup>
Conductor cross section flexible max.	16 mm <sup>2</sup>
Conductor cross section AWG min.	14
Conductor cross section AWG max.	4
Conductor cross section flexible, with ferrule without plastic sleeve min.	1.5 mm <sup>2</sup>
Conductor cross section flexible, with ferrule without plastic sleeve max.	16 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve min.	1.5 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve max.	16 mm <sup>2</sup>
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	1.5 mm <sup>2</sup>
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	4 mm <sup>2</sup>
Stripping length	18 mm
Connection side	Inside
Connection method	Cable lug connection

### Standards and Regulations

Connection in acc. with standard	UL
	IEC 60947-7-1
Flammability rating according to UL 94	V0

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---

# Panel feed-through terminal block - PWO 16-POT - 1705653

## Technical data

### Environmental Product Compliance

	No hazardous substances above threshold values
--	--

## Approvals


### Approvals


#### Approvals


UL Recognized / VDE Gutachten mit Fertigungsüberwachung / EAC

#### Ex Approvals

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 60425
	B	C	
mm <sup>2</sup> /AWG/kcmil	14-4	14-4	
Nominal current I <sub>N</sub>	66 A	66 A	
Nominal voltage U <sub>N</sub>	600 V	600 V	

VDE Gutachten mit Fertigungsüberwachung		<a href="http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx">http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx</a>	40039989
mm <sup>2</sup> /AWG/kcmil	1.5-16		
Nominal current I <sub>N</sub>	76 A		
Nominal voltage U <sub>N</sub>	1000 V		

EAC		B.01742
-----	---	---------